imagePROGRAFPRO-1000

Great quality printing to match your passion

A desktop size printer to serve professional photographers and aspiring amateurs. Print in stunning quality with a 12-ink pigment based system up to A2.





















- Bring your images to life with stunning prints that reproduce the detail and colour you work so hard to capture.
- Print up to A2 with colour calibration on a variety of paper, including glossy, matte, fine art or canvas.
- Using LUCIA PRO pigment inks, colours are richer and blacks are deeper, producing prints that are faithful to your images.
- With compatibility for a full range of devices and platforms, print your images with ease from PCs, smartphones, or the cloud.
- The Print Studio Pro plug-in lets you print effortlessly from professional editing software such as Adobe Lightroom®, Photoshop® and Canon's Digital Photo Professional.



PRO-1000 A2 CUT SHEET

LUCIA PRO 12 INKS

CHROMA OPTIMIZER

1.28" PRINT HEAD

2,400 x 1,200 DPI

INBUILT COLOUR CALIBRATION

PRINT PLUG-IN FOR PHOTO APPLICATIONS

USB,WIFI & ETHERNET CONNECTIVITY

USER-FRIENDLY COLOUR DISPLAY



Technical Specifications

imagePROGRAFPRO-1000

PRODUCT SPECIFICATION

Ink Type

Maximum Print Resolution [1]

Printing Speed [2]

Dimensions, Weight

Power Supply

Operational Environment

Acoustic Noise

Operation Panel Display

Memory

INTERFACE TYPE & SOFTWARE

Supported Operating Systems [7]

Supported Mobile Systems

Interface

Wireless LAN

Smart device & Cloud apps

Camera direct

Software

PRINT HEAD

Туре Head Configuration

Nozzle Pitch

Nozzle per Chip

Droplet Size

INK TANK Model

Page vield (4 x 6" PT-101) [8]

12 x Pigment : MBK/PBK/C/M/Y/PC/PM/GY/PGY/R/B/CO

2,400 x 1,200 dpi

A2 (LU-101 colour): Approx. 3 min 35 sec A2 (PT-101 colour or mono): Approx. 6 min

Approx. $723 \times 433 \times 285$ mm Weight approx. 32 kg (including print head and inks)

AC 100-240V (50-60Hz) Power consumption (approx 37W) [3] Standby consumption (approx 2.5W) Power off (approx 0.4W)

Temperature: 5-35°C, Humidity: 10-90%RH (no dew condensation) [4]

approx. 41.0 dB(A) - Photo (4 x 6") $^{[5]}$ approx. 40.8 Db(A) - Document (A4. B/W), Quiet Mode OFF $^{[6]}$ approx. 40.4 Db(A) - Document (A4. B/W), Quiet Mode ON

3.0" (320 x 240 TFT LCD), Key x 13, LED x 2

21 Languages Selectable: Japanese / English / German / Italian / Spanish / Portuguese / Dutch / Polish / Russian / Danish / Norwegian / Swedish / Finnish / Czech / Simplified Chinese / Traditional Chinese / Hungarian / Thai / Indonesian / French

/ Turkish

1GB

Windows 32bit: Windows Vista, Windows 7, Windows 8, Windows 8.1, Windows 10

Windows Server 2008

Windows 64bit: Windows 7, Windows 8, Windows 8.1,

Windows 10
Windows Server 2008/2008R2, Windows Server 2012/2012R2
*Windows RT(Windows 8 ARM version) is not supported

Macintosh OS10.7.5 -OS10.10.x

iOS Android

Hi Speed USB Type: Built-in

USB 2.0 High-Speed Full Speed (12 Mbit/sec), High Speed (480 Mbit/sec), Bulk transfer

IEEE802.11n IEEE802.11g IEEE802.11b

Type Built-in: IEEE 802.3 10base-T IEEE 802.3u 100base-TX Auto-Negotiation

Canon PRINT app (iOS or Android)
Pro Gallery Print app (iPad only)
PIXMA Cloud Link
Apple AirPrint
Google Cloud Print Wi-Fi PictBridge

Print Studio Pro. Quick Utility Toolbox, Media Configuration Tool. Account Manager, Device Management Console

Canon Bubbleiet on Demand

12 colours integrated type (4 colours chips x 3)

600dni x 2

1,536 nozzles x 12 colours, includes Non-firing nozzle detection and compensation system

4 Picoliter per colour

LUCIA PRO Ink Tanks:

PFI-1000 MBK/PBK/C/M/Y/PC/PM/GY/PGY/R/B/C

MBK/PBK/C/M/YPC/PM/GY/PG/ Number of 10cm x 15cm photos Matte Black (MBK): 5490 photos* Photo Black (PBK): 2205 photos* Grey (GY): 1465 photos* Photo Grey (PGY): 3165 photos* Photo Gyan (PC): 5140 photos* Cyan (C): 5025 photos* Photo Magenta (PM): 3755 photos Magenta (M): 5885 photos* Yellow (Y): 3365 photos Red (R): 5355 photos* Blue (B): 4875 photos* Chroma Optimizer (CO): 680 photo Chroma Optimizer (CO): 680 photos

* Estimated Supplemental Yield

Page yield (A2 PT-101) [8]

MEDIA HANDLING

Number of A2 colour photos Number of A2 colour photos Matte Black (MBK): 1600 photos* Photo Black (MBK): 256 photos* Grey (GY): 106 photos* 270 photos* Photo Grey (PGY): 270 photos* Photo Cyan (PC): 600 photos* Cyan (C): 675 photos* Photo Magenta (PM): 374 photos* Magenta (M): 955 photos* Yellow (Y): 329 photos Red (R): 935 photos* Blue (B): 545 photos* Chroma Optimizer (CO): 97 photos*

* Estimated Supplemental Yield

Media Feeding Rear tray / Manual feed slot

Plain Paper, Photo Paper Plus Glossy II, Photo Paper Pro Platinum, Media Type

Photo Paper Pro Luster, Photo Paper Plus Semi-Gloss, Photo Paper Pro Premium Matte, Matte Photo Paper, Other Fine Art, Canvas and Glossy Photo Papers

A5, A4, A3, A3+, A2, B5, B4, B3, $4\times6"$, $5\times7"$, $8\times10"$, $10\times12"$, $14\times17"$, $17\times22"$, LTR, LGL, LDR Media size **Media Thickness**

Manual feed slot: 254 mm

Rear tray: Plain paper 64-105g/m², Canon specialty paper Max.

Recommended - Top margin: 57 mm, Bottom margin: 55 mm, Left / Right: 3.4 mm (LTR / LGL - Left margin: 6.4 mm, Right margin: 6.3 mm)

Printable area - Top margin 3 mm, Bottom margin 5 mm, Left / Right margin 3.4 mm (LTR / LGL - Left margin: 6.4 mm, Right margin: 6.3 mm)

A4, A3, A3+, A2, 4 x 6", 5 x 7", 8 x 10", 10 x 12", 14 x 17", 17 x 22", LTR

300 g/m², Rear tray thickness: 0.1-0.3 mm Manual feed slot: Canon specialty paper Max. 400 g/m², Manual feed thickness: 0.1-0.7 mm

Rear tray: 89-432 mm, Manual feed slot: 203.2-432 mm Media Width Rear tray: 127 mm

594 mm

Minimal Printable Paper Length

Maximum Printable Paper Length

Margins (Top, Bottoms, Sides)

Media Width for Borderless Printing [8]

WHAT'S IN THE BOX?

imagePROGRAF PRO-1000 Power Cord Print Head

Print Head I2 individual ink tanks Sample Media: LU-101 A3 x 5 Sheets Head alignment media: MP-101 A4 x 2 Sheets Setup CD-ROM (CD only for Windows - Mac drivers available

PFI-1000 MBK/PBK/C/M/Y/PC/PM/GY/PGY/R/B/CO (80 ml)

online*) Starter guide

*All drivers and mobile apps are available online at

CONSUMABLES Ink Tank

Maintenance Cartridge

MC-20

[1] Ink droplets can be placed with a pitch of 1/2400 inch at minimum.

^[21] Print speed is based on the default setting using ISO/JIS-SCID N5 and does not take into account data processing time on host computer. Print speed may vary depending on system configuration, interface, software, document complexity, print mode, page coverage, type of paper used etc.

 $^{\hbox{\scriptsize [3]}}$ When printing ISO/JIS-SCID N2 pattern on A4 size Photo Paper Pro Platinum (PT-101) using default settings.

[4] The performance of the printer may be reduced under certain temperature and humidity conditions.

[8] Declared yield value in accordance with ISO/IEC 29103. Values obtained by continuous printing.

[5] When printing ISO/JIS-SCID N2 pattern on Photo Paper Pro Platinum using default settings

[6] Acoustic Noise is measured based on ISO7779 standard. [7] Minimum system requirements is according to that of OS and application software used

Specifications are subject to change without notice.



